



SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Pantone Color: 7529C~7530C

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
1252WR-02P	1.25	3.75
1252WR-03P	2.50	5.00
1252WR-04P	3.75	6.25
1252WR-05P	5.00	7.50
1252WR-06P	6.25	8.75
1252WR-07P	7.50	10.00
1252WR-08P	8.75	11.25
1252WR-09P	10.00	12.50
1252WR-10P	11.25	13.75
1252WR-11P	12.50	15.00
1252WR-12P	13.75	16.25
1252WR-13P	15.00	17.50
1252WR-14P	16.25	18.75
1252WR-15P	17.50	20.00

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP01-1252WR-NP
CHECKED			TITLE:	1.25mm PITCH 90°
APPROVALS			UNIT:	mm
TOLERANCES ARE		30~ ⁰ / ₁₀ ±0.30	SCALE:	1:1
		10~30 ±0.20	DRAWING NO.	
		5~10 ±0.15		
		~ 5 ±0.10		
		ANGLE		PROJ.
		±2'		SHEET 1 OF 1

