




Poles	DIM.A	DIM.B	DIM.C
2P	4.25	1.25	7.3
3P	5.50	2.50	8.5
4P	6.75	3.75	9.8
5P	8.00	5.00	11.0
6P	9.25	6.25	12.3
7P	10.50	7.50	13.5
8P	11.75	8.75	14.8
9P	13.00	10.00	16.0
10P	14.25	11.25	17.3
11P	15.50	12.50	18.5
12P	16.75	13.75	19.8
13P	18.00	15.00	21.0
14P	19.25	16.25	22.3
15P	20.50	17.50	23.5
16P	21.75	18.75	24.8



### ■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG.#28~#32  
Applicable Wire: AWG.#28~#32
  - ◆ 额定电压: 125V DC/AC(rms)  
Rated voltage: 125V DC/AC(rms)
  - ◆ 额定电流: 1A (AWG.#28)  
Rated Current: 1A (AWG.#28)
  - ◆ 耐压值: 250V AC/minute  
Withstand voltage: 250V AC/minute
  - ◆ 工作温度: -40°C ~ +85°C  
Working Temp : -40°C ~ +85°C
  - ◆ 绝缘电阻: ≥100 MΩ  
Insulation resistance: ≥100 MΩ
  - ◆ 接触电阻: ≤20 mΩ  
Contact resistance: ≤20 mΩ
- 材料 MATERIAL
- ◆ 绝缘体: 尼龙9T, UL94-V0  
Insulator: PA9T, UL94-V0
  - ◆ 接触针: 磷铜  
Contact PIN: Phosphor bronze
  - ◆ 焊片: 磷铜  
Solder tab: Phosphor bronze

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2017.09.13	1. 25mm SMT 立式	
CHECKED			PART NO. GP01-1250WVS-NP	
APPROVALS			SCALE: 1:1	
TOLERANCES ARE			PROJ. SHEET 1 OF 1	
30~以上	±0.30	ANGLE		
10~30	±0.20	UNIT: mm		
5~10	±0.15	DRAWING NO.		
~ 5	±0.10			



深圳市联丰电子有限公司  
SHENZHEN LINFENG ELECTRONIC CO.,LTD