



P. C. B LAYOUT

Technical Data
 Material: Pin(outer sleeve):Brass, machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated:2 μ m/80 μ "Ni, 5 μ m/200 μ "Sn
 Gold Plated:2 μ m"/80 μ "Ni, 0.8 μ " gold
 Insulator:PPS UL94V-0

Electrical:
 Current rating:3Amps/contact max.
 Contact resistance: $\leq 4m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Dielectric Withstanding Voltage:1000V AV Min
 Operating voltage:60VAC/DC

Mechanical:
 Operating temperature:-40° C to+105° C
 Soldering temperature:+255° C
 Critical Dimensions:⊗

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP22-2520WV-XP-1000C
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ: 1 OF 1
TOLERANCES ARE		30 μ 以上	±0.30	ANGLE
		10~30	±0.20	±2°
		5~10	±0.15	
		~ 5	±0.10	
ECN NO.	REV.	DATE.	DESCRIPTION.	
	A		NEW	
			CHANGE.	
			CHECK.	
			APPRO.	