



RECOMMENDED P. C. B LAYOUT

SPECIFICATIONS  
 Current Rating: 2Amps  
 Insulator resistance: 5000 Megchms min.  
 Dielectric Withstanding: AC 500V  
 Operating Temperature:  $-40^{\circ}$  to  $+105^{\circ}$  C  
 Contact Material: Phosphor Bronzs  
 Insulator Material: NYLON-6T  
 Plating: Gold Flash  
 Unspecified tolerance:  $\pm 0.20$

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LIANFENG ELECTRONIC CO.,LTD			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	FEMALE HEADER PITCH1.27*4.3mm SMD	PART NO.	GP25-1272WVS-2XNP-1
CHECKED			ANGLE	$\pm 2^{\circ}$	UNIT:	mm
APPROVALS			SCALE:	1:1	PROJ:	
TOLERANCES ARE			30~ $\phi$ 以上	$\pm 0.30$	DRAWING NO.	
			10~30	$\pm 0.20$	SHEET	1 OF 1
			5~10	$\pm 0.15$		
			~ 5	$\pm 0.10$		