



PCB Layout Diagram

Top View

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
1	HOUSING	1	LCP	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO. GP07-CR2032-02	
CHECKED			SCALE: 1:1	
APPROVALS			PROJ. SHEET 1 OF 1	
TOLERANCES ARE		30~φ±	±0.30	ANGLE
		10~30	±0.20	UNIT: mm
		5~10	±0.15	SCALE: 1:1
		~ 5	±0.10	PROJ. SHEET 1 OF 1


深圳市联丰电子有限公司
 SHENZHEN LINENGYING ELECTRONIC CO.,LTD

- NOTE:
- MATERIAL:
 - HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
 - CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: Sn100u")
 - ELECTRIC:
 - CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - OPERATING TEMPERATURE: -25° C ~ +85° C
- SEE ORDERING INFORMATION