



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE
- (SURFACE PLATING: Au* μ)

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25 °C ~ +85 °C

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
1	HOUSING	1	PPS	BROWN
	PART NAME	Q' TV	MATERIAL	PLATING & COLOR
	ECN NO.	REV.	DATE.	DESCRIPTION.
		A		NEW
				CHANGE.
				CHECK.
				APPRO.

APPROVALS		DATE	TITILE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	电池座 SONY SMT	
CHECKED			PART NO.	GP07-CR2032-14
APPROVALS			SCALE:	1:1
TOLERANCES ARE		ANGLE	UNIT:	mm
30 ^{UM} 以上	±0.30	±2°	DRAWING NO.	
10~30	±0.20		PROJ:	
5~10	±0.15		SHEET	1 OF 1
~ 5	±0.10			



深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD