



PCB Layout Diagram  
Top View

- NOTE:
1. MATERIAL:
    - a. HOUSING: PA66
    - b. CONTACT: PHOSPHOR BRONZE  
(SURFACE PLATING: Sn 100u")
  2. ELECTRIC:
    - a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
    - b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
    - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
    - d. OPERATING TEMPERATURE: -25° C ~ +85° C

SEE ORDERING INFORMATION

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.25MM	Sn-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.25MM	Sn-Plating
1	HOUSING	1	PA66	BLACK
VO	PART NAME	0' TY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LINFENG ELECTRONIC CO.,LTD			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	电池座 立式		
CHECKED			PART NO.	GP07-CR2430-02		
APPROVALS			UNIT:	mm		
TOLERANCES ARE		30~以上 ±0.30	SCALE:	1:1		
		10~30 ±0.20		PROJ.		
		5~10 ±0.15	DRAWING NO.			
		~ 5 ±0.10		SHEET 1 OF 1		
			ANGLE	±2°		