



NOTE:
 1. MATERIAL:
 a. HOUSING: LCP UL94V-0
 b. CONTACT: PHOSPHOR BRONZE
 (SURFACE PLATING: Sn100u"-120u")
 SEE ORDERING INFORMATION
 2. ELECTRIC:
 a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 d. OPERATING TEMPERATURE: -25°C ~ +85°C

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	
CHECKED			SCALE: 1:1	
APPROVALS			PROJ:	
TOLERANCES ARE		30~以上	±0.30	ANGLE
		10~30	±0.20	UNIT: mm
		5~10	±0.15	SCALE: 1:1
		~ 5	±0.10	PROJ:
CHANGE.	CHECK.	APPRO.	DRAWING NO.	SHEET 1 OF 1

 **深圳市联丰电子有限公司**
 SHENZHEN LINFENG ELECTRONIC CO.,LTD