



NOTE:
 1.MATERIAL:
 a.HOUSING:PBT
 b.CONTACT:Mn Steel
 (SURFACE PLATING: Ni100u"-120u")
 SEE ORDERING INFORMATION
 2.ELECTRIC:
 a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 d.OPERATING TEMPERATURE: -25°C~ +85°C

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LINFENG ELECTRONIC CO.,LTD			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	*****		
CHECKED			PART NO.	GP07-CR2032-17		
APPROVALS			UNIT: mm	SCALE: 1:1	PROJ:	
TOLERANCES ARE		30~φL ±0.30	ANGLE	±2°	DRAWING NO.	
		10~30 ±0.20				
		5~10 ±0.15				
		~ 5 ±0.10				